


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED
1	CH'D MATERIAL FROM 41L40 PER D.W.	7/27/10	RJC	DW



### SPLINE DATA

TYPE	EXTERNAL
NO. OF TEETH	34
DIA. PITCH	16/21
PITCH DIA.	2.125 REF.
PRESSURE ANGLE	20°
CIR. THICKNESS (REF.)	.095/.090
PIN DIA.	.120
DIA. OVER BETWEEN PINS	2.310 - 2.299
TYPE OF FIT	SIDE

RED BARN MACHINE	
TITLE ARBOR SPLINE	
DWG NO. RBA9965	REV 1
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1	DRAWN BY: CLOUGH APPROVED <i>D Weil</i> HEAT TREAT FINISH BLACK OXIDE SPEC USED ON MODEL
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE NTS	DATE 1-14-10
SHEET 1 of 1	

ASSY QTY	ASSY QTY	B/O	PART #	QTY	DESCRIPTION	MATERIAL	B/O INFORMATION OR SPECIFICATIONS
				1	ARBOR SPLINE	4140 Q&T	Ø2-1/2 x 8-1/4
	ASSY #						

